

Click to view Poster Panel 1 in PDF format (1.98 MB)

Click to view Poster Panel 2 in PDF format (4.29 MB)

PS Geological Sequestration Capacity in the Cambrian Mount Simon Sandstone: Assessment and Feasibility in the Michigan Basin, USA*

David A. Barnes¹, Stephen Kelly¹ and Diana H. Bacon²

Search and Discovery Article #80062 (2009)

Posted October 30, 2009

*Adapted from poster presentation at AAPG Convention, Denver, Colorado, June 7-10, 2009

¹Geosciences, Western Michigan University, Kalamazoo, MI (barnes@wmich.edu)

²Battelle Pacific Northwest Division, Richland, WA

Abstract

Geological sequestration (GS) potential in the Cambrian Mt. Simon Sandstone is substantial in the Midwest, USA, with tens of billions of metric tons of CO₂ storage capacity estimated in recent studies conducted throughout the region. This study presents the results of ongoing assessment of the Mt. Simon Sandstone Geological Sequestration System (GSS) in the Michigan basin, USA. Investigations were undertaken to refine regional GS capacity estimates using subsurface geological data and establish site specific characteristics and feasibility of GS for large, stationary emission sources in Michigan, although no capture facilities are now in place. Although the Mt. Simon constitutes a major GS resource in much of the state, this injection zone may have little effective porosity in the central Michigan basin below approximately 1.8 to 2.0 km due to complex diagenetic alteration. Lateral and vertical facies changes in the basin also result in substantial variation in fundamental rock properties, petrophysics, and storage capacity.

Using methodology modified from the Carbon Sequestration Atlas of the US and Canada (CSAUS & C), estimates of storage capacity of the Mt. Simon Sandstone in the most prospective areas of Michigan are as high as 14,000 metric tons of CO₂ per acre. Numerical simulations of CO₂ injection were conducted using the STOMP-CO₂ simulator to assess the potential for large volume GS in one of

these most promising areas of the state using existing core and well data from waste injection wells. Using numerical injection simulation model parameters including: 1) injection rate of 10 MMT/yr for 50 years, 2) recovery period of 50 years, 3) injection interval between 1574-1768 m, 4) well diameter of 8 5/8" casing, 5) hydrostatic gradient of 0.49 psi/ft, 6) temperature of 50C, 7) brine composition of 300,000 ppm TDS; the resulting model predicted: 1) ½ space 2D Plume Dimensions after 100 years (50 years active injection, 50 years recovery) equal to ~9 km (5.4 mi), 2) active injection flow rate of ~160m/yr, and 3) Recovery flow rate of ~20 m/yr. Although these results suggest that the Mt. Simon GSS has the capacity to accept the large volume, CO₂ output of a typical coal-fired electric power plant in a small number of injection wells, further sensitivity analysis and field validation will be needed before such high injection potential can be verified.

References

Blakey, R., Northern Arizona University, Dr. Ronald C. Blakey, Department of Geology Faculty: Web accessed 25 September 2009 <http://www4.nau.edu/geology/master.html?http://www4.nau.edu/geology/blakey.html>

Coalson, E.B., D.J. Hartmann, J.B. Thomas, 1985, Productive characteristics of common reservoir porosity types: Bulletin of the South Texas Geological Society, v. 25/6, p. 35-51.

Cosentino, L., 2001, Integrated Reservoir Studies, Editions Technip, Paris: Bulletin of Canadian Petroleum Geology, v.51/2; p. 209-211. DOI: 10.2113/51.2.209

Odom, I.E., 1975, Feldspar-Grain Size Relations in Cambrian Arenites, Upper Mississippi Valley: Journal of Sedimentary Petrology, v. 45/3, p. 636-650.

Runkel, A.C., J.F. Miller, R.M. McKay, A.R. Palmer, and J.F. Taylor, 2007, High-resolution sequence stratigraphy of lower Paleozoic sheet sandstones in central North America: The role of special conditions of cratonic interiors in development of stratal architecture: Geological Society of America Bulletin, v. 119/7-8, p. 860-881.