#### My Source Rock is Now My Reservoir - Geologic and Petrophysical Characterization of Shale-Gas Reservoirs\*

Q.R. Passey<sup>1</sup>, K.M. Bohacs<sup>1</sup>, W.L. Esch<sup>1</sup>, R. Klimentidis<sup>1</sup>, and S. Sinha<sup>1</sup>

Search and Discovery Article #80231 (2012)\*\*
Posted June 25, 2012

\*Adapted from 2011-2012 AAPG Distinguished Lecture for AAPG European Region.

<sup>1</sup>ExxonMobil Upstream Research Co., Houston, Texas (Quinn.r.passey@exxonmobil.com)

#### **Abstract**

Many currently producing shale-gas reservoirs are overmature oil-prone source rocks containing Type I or Type II kerogen. Key characterization parameters are: total organic carbon (TOC), maturity level (vitrinite reflectance), mineralogy, thickness, and organic matter type (OMT). Recent studies indicate that although organic-rich shale-gas formations may be hundreds of meters in gross thickness (and may appear largely homogeneous), the vertical variability in the organic richness and mineralogy can vary on relatively short vertical scales (e.g., 10's centimeters - 1 meter). The vertical heterogeneity observed can be directly tied back to geologic and biotic conditions when deposited. The accumulation of organic-rich rocks (ORRs) is a complex function of many interacting processes that can be summarized by three main control variables: rate of production, rate of destruction, and rate of dilution. The marine realm includes three physiographic settings that accumulate significant organic-matter-rich rocks: constructional shelf margin, platform/ramp, and continental slope/basin. In general, the fundamental geologic building block of shale-gas reservoirs is the parasequence, or its equivalent, and commonly 10's to 100's of parasequences comprise the organic-rich formation whose lateral continuity can be estimated, using techniques and models developed for source rocks.

Many geochemical and petrophysical techniques developed to characterize organic-rich source rocks in the oil-generation window (Ro=0.5-1.0) can be applied, sometimes with modification, to shale-gas reservoirs that currently exhibit high thermal maturity (Ro=1.1 - 4.0). Well logs can be used to calculate TOC, porosity, and hydrocarbon saturation, but in clay-rich mudstones, the fundamental definition of porosity is complicated by the high surface area of clay minerals (external and sometimes internal), the volume of surface water, and the presence of water held by capillary forces in very small pores between silt and clay size mineral grains. Moreover, SEM images of ion-beam-milled samples reveal a separate nano-porosity system contained within the organic matter, and the gas may be largely contained in these organic pores.

The use of high-vertical-resolution standard logs and borehole image logs enhances the interpretation of vertically heterogenous shale-gas

<sup>\*\*</sup>AAPG©2012 Serial rights given by author. For all other rights contact author directly.

formations. It is important to keep in mind that kerogen occupies a much larger volume percent (vol%) than is indicated by the TOC weight percent (wt%); this is because of the low grain density of the organic matter (typically 1.1-1.4 g/cc) compared to that of common rock-forming minerals (2.6-2.8 g/cc). Well logs play a critical role in characterizing and quantifying shale-gas resources.

#### References

Bohacs, K.M., G.J. Grawbowski, A.R. Carroll, P.J. Mankeiwitz, K.J. Miskell-Gerhardt, J.R. Schwalbach, M.B. Wegner, and J.A. Simo, 2005, Production, Destruction, and Dilution – the Many Paths to Source-Rock Development, *in* N.B. Harris, (ed.), The deposition of organic-carbon-rich sediments; models, mechanisms, and consequences: SEPM Special Publication 82, p. 61-101.

Creaney, S., and Q.R. Passey, 1993, Recurring patterns of total organic carbon and source rock quality within a sequence stratigraphic framework: AAPG Bulletin, v. 77/3, p. 386-401.

Gale, J.F.W., R.M. Reed, and J. Holder, 2007, Natural fractures in the Barnett Shale and their importance for hydraulic fracture treatments: AAPG Bulletin, v. 91/4, p. 603-622.

Momper, J.A., 1978, Oil Migration Limitations Suggested by Geological and Geochemical Considerations: AAPG Continuing Education Course Note Series, v. 8, p. B1-B60.

Passey, Q.R., K. Bohacs, R.E. Klimentidis, W.L. Esch, and S. Sinha, 2011, My source rock is now my shale-gas reservoir-characterization of organic-rich rocks: AAPG Annual convention, April 10-13, 2011, Houston, Texas (Abstract). Search and Discovery Article #90124. Web accessed 22 June 2012.

http://www.searchanddiscovery.com/abstracts/html/2011/annual/abstracts/Passey.html?q=%2BtextStrip%3A%22my+source+rock%22

Passey, Q.R., K.M. Bohacs, W.L. Esch, R.E. Klimentidis, and S. Sinha, 2010, From oil-prone source rock to gas-producing shale reservoir – geologic and petrophysical characterization of unconventional shale-gas reservoirs: SPE 131350, 29 p. Web accessed 18 June 2012. (<a href="http://www.onepetro.org/mslib/servlet/onepetropreview?id=SPE-131350-MS">http://www.onepetro.org/mslib/servlet/onepetropreview?id=SPE-131350-MS</a>)

Passey, Q.R., S. Creaney, J.B. Kulla, F.J. Moretti, and J.D. Stroud, 1990, A practical model for organic richness from porosity and resistivity logs: AAPG Bulletin, v. 74, p. 1777-1794.

Spears, R.W., D. Dudus, A. Foulds, Q. Passey, S. Sinha, and W.L. Esch, 2011, Shale gas core analysis: strategies for normalizing between laboratories and a clear need for standard materials: 52<sup>nd</sup> Annual SPWLA Logging Symposium Transactions, Paper A, 11 p.

Tissot, B.P., and D.H. Welte, 1984, Petroleum Formation and Occurrence: Springer-Verlag, Berlin, Germany, 699 p.




# My Source Rock is Now My Reservoir - Geologic and Petrophysical Characterization of Shale-Gas Reservoirs

Q. R. Passey, K. M. Bohacs, W. L. Esch, R. Klimentidis, and S. Sinha, ExxonMobil Upstream Research Co.



#### **Organic Matter Type**







(After Tissot and Welte, 1984; Passey et al., 2010)

### Maturity (LOM/Ro) – Type II Kerogen and Coal Rank









#### Coal Rank




### Vertical Variability Scale of cm to meters








#### **Controls On Organic-Richness**




# Simple Model for Marine Organic Enrichment






### Stacked TOC Triangles (2 Parasequences)





# Vertical Variation in TOC from Well Log Response






#### **Marine Source Rock Settings**




TOC HI

Constructional Shelf Margin

≅ Maximum Transgression (uTST-IHST)



# TOC/Parasequence Stacking in Outcrop




#### Turner Falls Roadcut (Lower Woodford)

Off US 77 south of Exit 51 (I-35)


(N 34° 26.675' W 97° 7.814')






(Includes data from Lo and Bohacs, 1990, pers. comm.)


#### Woodford Shale – 20 wt% TOC → 40 vol% Kerogen





#### Apply threshold


Fluorescing kerogen
(Tasmanites cysts of marine algae)




(After Passey et al., 2010)


#### **Marine Source Rock Settings**








# Maturity Effect on Well Log Response in Organic-rich Intervals




### Systematic vertical variation in TOC






#### Stacking Patterns within Mowry Shale?




#### **Correlation of TOC Maxima (and Parasequences) Mowry**






# Parasequence Lithofacies Stacking Pattern






# Analytical Methods - GRI Crushed Rock vs Plug Porosity




#### Sampling for Lab Comparison




- Preserved shale samples were used in the studies
- Parts of same sample were sent to 3-5 different commercial laboratories for bulk and grain densities, GRI porosity, GRI perm and saturation measurements






### Comparison of "Reported Porosity" from Different Labs





### Definition of Total & Effective Porosity for Shale-gas Reservoirs




### Comparison of "GRI" Total Porosity from Different Labs






★ Total Porosity Measurements now within ~1p.u.



**Does Rock Composition Matter?** 




### **Key Parameters for Shale Gas Sample Evaluation**



- Total Organic Carbon (TOC) wt%
- Maturity (Ro %)
  - -Vitrinite Reflectance Equivalent
  - Biomarkers maturity indicator
  - Carbon Isotopes related to maturity
- Geochemical parameters (HC type and quality)
  - Fluid inclusions
  - Wetness (C2-C5)
  - API Gravity (tight oil)
- Total Porosity crushed rock total porosity method
- Water Saturation (total)
- Adsorbed gas volume (scf/ton)
- Free gas typically calculated from logs
- Permeability steady state flow recommended
- Microscopy
  - Thin Sections optical microscopy
  - Scanning Electron Microscopy (SEM/EDS)
  - Focus Ion Beam SEM
- Lithology/mineralogy
  - XRD/XRF
- Geomechanical Properties (Young's Modulus, Poisson's ratio)


# TOC from ∆logR and Borehole Image Log Response






### **TOC versus Total Porosity** in Gas-bearing Mudrocks






### Porosity versus Gas-filled Porosity in Shale-Gas Reservoir




#### **TOC and Sg are Correlated**





### Interclay Porosity – Filled with Water Organic Pores – Filled with Gas







TOC =5.6 wt% Ro =2.2  $\phi_t \cong$  15 p.u. (~ 8 p.u. water)


# Recrystalized Biogenic Silica and Pores in Organic Matter






# Pore-size Comparison – Fine Sandstone versus Organic-matter





### **Hypothetical Distribution** of Gas and Water






### Adsorbed Gas Fraction Higher in Small Pores (Surface to Volume)



40 nm Pore S/V = 0.15

Free Gas > (Adsorbed)



4 nm Pore S/V = 1.5 Adsorbed ~ Free Gas




2 nm Pore S/V = 3.1 Adsorbed > (Free Gas)

#### **TOC** wt% ≠ **TOC** vol%




#### For a "Typical" Shale Gas the current TOC = 5 wt%




10 vol% TOC (Solid)

If 50 vol% of the original organic matter volume is now pores, the volume impacted by the current 5 wt% TOC is approximately 20 vol% of the rock.




~20 volume % of the rock

# 5-Lab Comparison – Porosity getting better but what about Permeability?






# Where is the oil in "Shale Oil"?




#### **Molecular Sizes and Organic Pores**





(After Momper, 1978)


### Woodford Shale – 20.9 wt% TOC



#### Porosity Evolution in Organic-rich Rocks







(Gale et al. 2007) Shale Oil (Ro 0.5-1.0) kerogen Carbonate 5 cm clay kerogen silt 500 μm 2012 AAPG Distinguished Lecture

#### Summary



- Shale-gas reservoirs are overmature oil-prone source rocks
- The parasequence is the fundamental building block of shale gas reservoirs
- Porosity, TOC, and gas content are all positively correlated for shale-gas reservoirs Ro 1-3+)
- Free gas likely to be largely in organic-matter porosity
- Gas-filled porosity (BVG) is better characterization term than
   Sg
- The porosity system for fluids in organic-rich systems evolves with increasing maturity and is influenced by matrix lithology

### For Further Information – SPE 131350





#### **SPE 131350**

#### From Oil-Prone Source Rock to Gas-Producing Shale Reservoir – Geologic and Petrophysical Characterization of Unconventional Shale-Gas Reservoirs

Q. R. Passey, K. M. Bohacs, W. L. Esch, R. Klimentidis, and S. Sinha, ExxonMobil Upstream Research Co.

Copyright 2010, Society of Petroleum Enginee

This paper was prepared for presentation at the CPS/SPE international Oil & Gas Conference and Exhibition in China held in Beilling, China, 8-10 June 2010

This paper was selected for presentation by a CPSIDEE program committee billowing review or information contained in an abstract submitted by the author(s). Contents of the paper have not been reviewed by the Society of Petroleum Engineers and are subject to correction by the author(s). The material does not necessarily reted any position of the Society of Petroleum Engineers and see subject to correction by the author(s). The material does not necessarily reted any position of the Society of Petroleum Engineers and see submitted Engineers is profitable. Permission to reproduce in print is restricted to an abstract of not more than 2000 words; illustrations may not be covered. The abstract must contain conspicuous acknowledwhere of convolution.

#### Abstract

Many currently producing shale-gas reservoirs are overmature oil-prone source rocks. Through burial and heating these reservoirs evolve from organic-matter-rich mud deposited in marine, lacustrine, or swamp environments. Key characterization parameters are: total organic carbon (TOC), maturity level (vitrinite reflectance), mineralogy, thickness, and organic matter type. Hydrogen-to-carbon (HI) and oxygen-to-carbon (OI) ratios are used to classify organic matter that ranges from oil-prone algal and herbaceous to gas-prone woody/coal/y material.

Although organic-matter-rich intervals can be hundreds of meters thick, vertical variability in TOC is high (<1-3 meters) and is controlled by stratigraphic and biotic factors. In general, the fundamental geologic building block of shale-gas reservoirs is the parasequence, and commonly 10's to 100's of parasequences comprise the organic-rich formation whose lateral continuity can be estimated using techniques and models developed for source rocks.

Typical analysis techniques for shale-gas reservoir rocks include: TOC, X-ray diffraction, adsorbed/canister gas, vitrinite reflectance, detailed core and thin-section descriptions, porosity, permeability, fluid saturation, and optical and electron microscopy. These sample-based results are combined with full well-log suites, including high resolution density and resistivity logs and borehole images, to fully characterize these formations. Porosity, fluid saturation, and permeability derived from core can be tied to log response; however, several studies have shown that the results obtained from different core analysis laboratories can vary significantly, reflecting differences in analytical technique, differences in definitions of fundamental rock and fluid properties, or the millimeter-scale variability common in mudstones that make it problematic to select multiple samples with identical attributes.

Porosity determination in shale-gas mudstones is complicated by very small pore sizes and, thus, large surface area (and associated surface water); moreover, smecthic clays that are commonly present in mud have interlayer water, but this clay family tends to be minimized in high maturity formations due to illitration. Finally, SEM images of ion-beam-milled samples reveal a separate nano-porosity system contained within the organic matter, possibly comprising >50% of the total porosity, and these pores may be hydrocarbon wet, at least during most of the thermal maturation process. A full understanding of the relation of porosity and gas content will result in development of optimized processes for hydrocarbon recovery in shale-gas reservoirs.

#### Introduction/Background

The term "unconventional reservoirs" covers a wide range of hydrocarbon-bearing formations and reservoir types that generally do not produce economic rates of hydrocarbons without stimulation. Common terms for such "unconventional" reservoirs include: Tight-Gas Sandstones, Gas Hydrates, Oil Shale formations, Heavy Oil Sandstones, and Shale Gas, among others. The focus of this paper is to discuss the geological genesis and characterization of the class of "unconventional" reservoirs commonly termed Shale Gas.

Shale is a term that has been applied to describe a wide variety of rocks that are composed of extremely fine-grained particles, typically less than 4 microns in diameter, but may contain variable amounts of silt-size particles (up to 62.5 microns). In

