

PS Geomechanical Analysis of CO₂ Sequestration in the Bakken Formation*

Ogochukwu Ozotta¹ and Mehdi Ostadhassan¹

Search and Discovery Article #80691 (2019)**

Posted July 29, 2019

*Adapted from poster presentation given at 2019 AAPG Annual Convention and Exhibition, San Antonio, Texas, May 19-22, 2019

**Datapages © 2019 Serial rights given by author. For all other rights contact author directly. DOI:10.1306/80691Ozotta2019

¹University of North Dakota, Grand Forks, North Dakota (ogochukwu_ozotta@yahoo.co.uk)

Abstract

The purpose of this research is to determine the integrity of the Bakken shales and the capability to resist the buoyancy-drive flow of CO₂ to avoid risk of leakage and excessive fracture length. The effect of CO₂ sequestration on the mechanical properties of the Middle-Bakken is evaluated by measuring the geomechanical index properties before and after soaking with CO₂. We investigate the impact of CO₂ sequestration on the mechanical parameters based on the sequestration time intervals and determine if CO₂ sequestration will reactivate faults in the Bakken Formation. This information will be used to develop appropriate injection strategy, estimate injection potential and quantifying injection-induced seismicity risk.



Cores will be derived from active wells producing from the Bakken Formation (Upper, Lower and Middle member) in North Dakota, precisely in Dunn and McKenzie counties. The uniaxial compressive test (UCS) and the triaxial compressive test will be conducted on the cores, a non-destructive test when load is gradually applied to the cores and a transducer connected to the cores to measure the acoustic emission and to analyze the mechanical changes and behavior of the cores. The cores will also be saturated with CO₂ for 2-90 days and the cores will be analyzed for changes in the geomechanical properties at various intervals. We expect the pores of the cores to change mechanically when exposed to CO₂. CT scans will provide internal pore structure of Bakken Formation cores to define the pattern of the changes. Scanning electron microscope (SEM) will be used to study the electron behavior in the internal structure of the cores.

Geomechanical Impacts of CO₂ Storage on Rock Properties and Potential for Fault Reactivation

Ogochukwu Ozotta (ogochukwu.ozotta@und.edu) and Mehdi Ostadhassan (mehdi.ostadhassan@und.edu)
Petroleum Engineering University of North Dakota


Introduction

Carbon sequestration and enhanced oil recovery has attracted a lot of concerns in the unconventional shale resources in the past few years. The use of fossil fuel in the past century has drastically increased CO₂ emission into the atmosphere. About 80% of global primary energy is from fossil fuel, and the demand for fossil fuel is on the increase to satisfy the basic human needs. A total of about 22x10⁹ tonnes CO₂/year is currently been emitted into the atmosphere globally. According to the EPA eGRID2016 database, as of 2016, U.S. emits about 2x10⁹ tonnes CO₂/year as shown below. Out of that North Dakota has about 37 x 10⁶ tonnes CO₂/year net generation of CO₂.




Location


The study site for the CO₂ sequestration in North Fork Oil & Gas field in the Western North Dakota shown in the figure below



Method




Experimental set up of acoustic emission monitoring, modified from Zhou et al (2018). This equipment will be used to measure V and S waves velocities to know how cracks are propagated on core plugs before and after CO₂ exposure, and to study how CO₂ sequestration will alter the porosity, permeability and hence the velocity of the rock.




Stress-strain diagram showing the stages of crack development. Modified from Eberhardt et al 1999. This graph will help to study the crack propagation, its threshold when axial load is applied to measure the core plug strength before and after CO₂ exposure. And CO₂ sequestration model to understand the underground formation (Adopted from EERC 2018). Failure of rock occurs when internal micro-cracks are initiated, expanded and eventually developed into macro-crack, which releases a strain energy as elastic waves known as the stress waves or acoustic emission. Acoustic emission is used to study the damage mechanics of rocks caused by crack initiation and propagation of cracks under an induced stress leading to sudden release of strain energy of the rock material.

Results



Bulk density plot of Well NO 24123 on blue from the NDIC database before CO₂ exposure, this information will be used to determine the best Formation, pressure, temperature for sequestration to mimic the formation properties at the laboratory.

Current and future work



Build and geological model of the field with all the formation properties. Run a simulation of CO₂ sequestration in the geological model to determine its injectivity, capacity, caprock integrity and potential for fault reactivation in the basin.

Acknowledgments

We acknowledge and thank the Petroleum Engineering department for the access to their laboratory and North Dakota Industrial Commission for the access to their web information.