

[Click to view poster in PDF format \(6.95 MB\)](#)

**PS Characterization of Springfield Coal Member of the Carbondale Formation (Pennsylvanian) in a CO<sub>2</sub> Sequestration Pilot - Illinois Basin - Tanquary Site\***

**David G. Morse<sup>1</sup>, Maria Mastalerz<sup>2</sup>, John A. Rupp<sup>2</sup> and Satya Harpalani<sup>3</sup>**

Search and Discovery Article #80059 (2009)

Posted October 15, 2009

\*Adapted from poster presentation at AAPG Annual Convention and Exhibition, Denver, Colorado, June 7-10, 2009

<sup>1</sup> Illinois State Geological Survey, Champaign, IL (<mailto:morse@isgs.uiuc.edu>)

<sup>2</sup> Indiana Geological Survey, Indiana University, Bloomington, IN

<sup>3</sup> College of Engineering, Southern Illinois University, Carbondale, IL

### **Abstract**

The potential for sequestering CO<sub>2</sub> in the largest bituminous coal reserve in the United States (Illinois Basin) is being assessed in southeastern Illinois as part of the U.S. Dept of Energy's Regional Sequestration Partnership program. To accomplish the main objectives of this test, which are to determine CO<sub>2</sub> injection rates and storage capacity, a detailed coal characterization program was developed in order to provide the best input into the COMET 3 Reservoir Simulator. At the Tanquary site, the targeted Springfield Coal is high volatile bituminous rank (R<sub>o</sub> average of 0.62%), 7 ft thick and occurs at 900 ft depth. The seam was examined in core from one injection and three observation wells spaced approximately 50 to 100 ft apart and oriented relative to the cleat directions.

Desorbed coal gas content from one foot core intervals varies from 150 to 210 scf/ton (dmmf) and consists generally of >92% CH<sub>4</sub> with lesser amounts of N<sub>2</sub> and then CO<sub>2</sub>. Coal maceral composition averaged 70.2% vitrinite, 3.6% liptinite, 13.9% inertinite and 7.3% mineral matter with considerable variation, particularly in inertinite content, from the top to the bottom of the seam. As the adsorption of CO<sub>2</sub> varies with maceral type, the abundance of different macerals significantly affects the sequestration potential, being greatest in the vitrinite-rich (bright) coal and decreasing significantly in the inertinite-rich (dull) coals. Coal cleats are well developed with 1 to 2 cm spacing and, may be partially mineralized with calcite and/or kaolinite fillings that decrease coal permeability. CH<sub>4</sub>, CO<sub>2</sub> and N<sub>2</sub> adsorption isotherms indicate at least 3 molecules of CO<sub>2</sub> can replace each displaced CH<sub>4</sub> molecule. High resolution open-hole logs through the coal reveal variation in the potential coal permeability with the shallow resistivity curve in the basal 2 feet showing much higher resistivity than the medium or deep curves, due to increased fresh water drilling fluid invasion into the near well bore compared

to the deeper more saline indigenous fluid. Gamma Ray and bulk density vary somewhat, reflecting differences in maceral, ash and pyrite content. Density porosity is fairly uniform, whereas neutron porosity, which is sensitive to hydrogen atoms, shows high variability. Because all the coal characteristics highlighted above will vary across the basin, it is critical to determine them around any injection site in order to best predict the potential for CO<sub>2</sub> injection.

## References

Demir, I., D.G. Morse, S.D. Elrick, C.A. Chenoweth, 2004, Delineation of the Coalbed Methane Resources of Illinois: Illinois State Geological Survey Circular 564, CD.

U.S. Department of Energy Office of Fossil Energy, National Energy Technology Laboratory, November 2008, Carbon Sequestration Atlas of the United States and Canada, Second Edition, 140 p.